



LIQUID TIGHT NYLON STRAIN RELIEFS

Simply push the cable through the liquid tight nylon strain relief and tighten dome nut for a quick installation. No disassembly is required. Available in many sizes and styles. The nylon body material is resistant to most common chemicals and solvents. Meets UL requirements (seal ring does not meet UL requirements), and exceeds NEMA 6 specifications if seal ring is used when installation is through a clearance hole.

Standard dome nut style can be used, or a flex nut type is available that can help prevent cable kinking. Straight-in styles in NPT sizes. Metric sizes and 90° elbow styles available on special order. Either thread into your panel or for applications with clearance holes, order the locking nut and seal ring separately. For best results, use the minimum size that fits your cable. Typical applications include use with service cord on page 11. Black color only.

Cable Dia. Min.	Cable Dia. Max.	Mounting Hole Sizes	Thread Size NPT	Dome Nut Stock No.	Flex Nut Stock No.	Lock Nut Stock No.	Seal Ring Stock No.
.11	.26	.49	1/4 (PG 7)	24608	24621	24644	24653
.08	.20	.49	1/4 (PG 7)	24609	24622	24644	24653
.16	.31	.68	3/8	24600	24615	24640	24650
.08	.24	.68	3/8	24601	24616	24640	24650
.24	.47	.83	1/2	24602	24617	24641	24651
.20	.35	.83	1/2	24603	24618	24641	24651
.51	.71	1.05	3/4	24604	24619	24642	24652
.35	.63	1.05	3/4	24605	24620	24642	24652
.71	.98	1.35	1	24606	---	24643	---
.51	.79	1.35	1	24607	---	24643	---

ORDERING NOTES:

- Order by Stock Number and quantity required.
- Optional locking nut required when mounted in a clearance hole (not threaded in place).

All dimensions in inches.



Dome Nut Style



Flex Nut Style



Optional locking nut and seal ring

3M™ SAFETY WALK™ TAPE

Stock No. 20870

3M™ Safety Walk Traction Treads help solve costly slip and fall problems before they begin, while improving product performance and safety. These anti-slip materials are effective in environments containing oil, grease and water.

Ease of application makes for instant protection. Self adhesive to any dry, clean surface. Available in 6" x 24" pieces. Especially popular in marine and heavy duty equipment applications.



SHOCK PROTECTED DEVICES UL LISTED

GFCI Plug User Attachable

Stock No. 10270

For rewiring your cords with a GFCI rainproof plug. Remove the old plug and replace it, for 12 through 18 ga conductors, 15 amps 120 Volts AC. Manual reset required after trip.



GFCI Plug and Cord Sets

Stock No. 10280

GFCI protected cord sets will provide protection for your non GFCI cords. Includes manual reset adapter, and 9 in. 14/3 cord. Rated 15 amps, 120 volts AC. Outdoor rated.



GFCI Cord with Circuit Breaker

Stock No. 10292

This GFCI cord is made for double protection featuring a GFCI and a triple outlet female with a built-in resettable circuit breaker. It has 2 ft. 12/3 SJTW-A cable. Rated 15 amps, 120 volt AC.

