




## Push-on Terminals



Typical Female insulated



Insulated Push-on



Typical male non-insulated

### Female push-on

Non-insulated

#### Butted Seam

<u>Part No.</u>	<u>Wire Gauge</u>	<u>Tab Size (Width &amp; Thickness)</u>	<u>Length</u>
30119	26-20	.110 x .020	0.535
30016	22-18	.187 x .020	0.573
30011	22-18	.250 x .032	0.658
31019	16-14	.110 x .020	0.573
31016	16-14	.187 x .020	0.573
31011	16-14	.250 x .032	0.658
32011	12-10	.250 x .032	0.700
32012	12-10	.375 x .050	0.930

Insulated

#### Vinyl


<u>Part No.</u>	<u>Wire Gauge</u>	<u>Tab Size (Width &amp; Thickness)</u>	<u>Length</u>
30516	22-18	.187 x .020	0.789
30511	22-18	.250 x .032	0.865
31519	16-14	.110 x .020	0.789
31516	16-14	.187 x .020	0.789
31511	16-14	.250 x .032	0.865
32511	12-10	.250 x .032	1.010
32512	12-10	.375 x .050	1.230

### Female push-on

Insulated



## Push-on Terminals



Typical Female insulated



Insulated Push-on



Typical male non-insulated

### Nylon

<u>Part No.</u>	<u>Wire Gauge</u>	<u>Tab Size (Width &amp; Thickness)</u>	<u>Length</u>
30716	22-18	.187 x .020	0.765
30711	22-18	.250 x .032	0.865
31719	16-14	.110 x .020	0.765
31716	16-14	.187 x .020	0.765
31711	16-14	.250 x .032	0.865
32711	12-10	.250 x .032	1.000

### Male push-on

#### Non-insulated

#### Butted Seam

<u>Part No.</u>	<u>Wire Gauge</u>	<u>Tab Size (Width &amp; Thickness)</u>	<u>Length</u>
30051	22-18	.187 x .020	0.630
30010	22-18	.250 x .032	0.722
31014	16-14	.187 x .020	0.630
31010	16-14	.250 x .032	0.725
32010	12-10	.250 x .032	0.770

#### Insulated

#### Vinyl

<u>Part No.</u>	<u>Wire Gauge</u>	<u>Tab Size (Width &amp; Thickness)</u>	<u>Length</u>
30551	22-18	.187 x .020	0.820
30510	22-18	.250 x .032	0.915
31551	16-14	.187 x .020	0.820
31510	16-14	.250 x .032	0.915
32510	12-10	.250 x .032	0.870


#### Insulated

#### Nylon

<u>Part No.</u>	<u>Wire Gauge</u>	<u>Tab Size (Width &amp; Thickness)</u>	<u>Length</u>
-----------------	-------------------	---	---------------




## Push-on Terminals



Typical Female insulated



Insulated Push-on



Typical male non-insulated

30751	22-18	.187 x .020	0.820
30710	22-18	.250 x .032	0.903
31751	16-14	.187 x .020	0.820
31710	16-14	.250 x .032	0.903
32710	12-10	.250 x .032	1.060

## 3M™ Scotchlok™ Disconnects - Nylon Insulated

### Nylon Insulated

#### Male Nylon Insulated

<u>Part No.</u>	<u>Wire Gauge</u>	<u>Tab Size (Width &amp; Thickness)</u>	<u>Length</u>
30550	22-18	.187 x .020	0.87
30512	22-18	.250 x .032	0.95
31550	16-14	.187 x .020	0.87
31512	16-14	.250 x .032	0.95
32514	12-10	.250 x .032	1.05

#### Male Nylon Insulated w/Extra Sleeve

<u>Part No.</u>	<u>Wire Gauge</u>	<u>Tab Size (Width &amp; Thickness)</u>	<u>Length</u>
30750	22-18	.187 x .020	0.87
30712	22-18	.250 x .032	0.95
31750	16-14	.187 x .020	0.87
31712	16-14	.250 x .032	0.95
32714	12-10	.250 x .032	1.05


## 3M™ Scotchlok™ Disconnects - Nylon Insulated

### Nylon Insulated

#### Female Nylon Insulated



## Push-on Terminals



Typical Female insulated



Insulated Push-on



Typical male non-insulated

<u>Part No.</u>	<u>Wire</u>	<u>Tab Size</u>	<u>Length</u>
	<u>Wire Gauge</u>	<u>(Width &amp; Thickness)</u>	
30612	26-20	.110 x .020	0.66
30518	22-18	.187 x .020	0.81
30513	22-18	.250 x .032	0.87
31518	16-14	.187 x .020	0.81
31513	16-14	.250 x .032	0.87
32515	12-10	.250 x .032	0.99

### Female Nylon Insulated w/Extra Sleeve

<u>Part No.</u>	<u>Wire</u>	<u>Tab Size</u>	<u>Length</u>
	<u>Wire Gauge</u>	<u>(Width &amp; Thickness)</u>	
30613	26-20	.110 x .020	0.66
30718	22-18	.187 x .020	0.765
30713	22-18	.250 x .032	0.87
31718	16-14	.187 x .020	0.81
31713	16-14	.250 x .032	0.87
32715	12-10	.250 x .032	0.99

### Perma-Seal™ Fully Insulated Push-ons

#### Male

<u>Part No.</u>	<u>Wire</u>	<u>Tab Size</u>	<u>Length</u>
	<u>Wire Gauge</u>	<u>(Width &amp; Thickness)</u>	
31772	16-14	.250 x .032	


### Perma-Seal™ Fully Insulated Push-ons

#### Female

<u>Part No.</u>	<u>Wire</u>	<u>Tab Size</u>	<u>Length</u>
	<u>Wire Gauge</u>	<u>(Width &amp; Thickness)</u>	
31773	16-14	.250 x .032	



## Push-on Terminals



Typical Female insulated



Insulated Push-on



Typical male non-insulated

Dimensions listed are a guide only and may not be exact. Dimensions may also change without notice. While efforts have been made to ensure the terminal dimensions listed are accurate, Waytek, Inc. does not warrant the accuracy of information included herein.