




Ring Terminals



Typical Insulated

Miniature 26-24 Gauge Ring Terminals

Non-Insulated

Butted Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
30100	26-24	0	0.366	0.150	0.121	.020
30101	26-24	2	0.366	0.150	0.121	.020
30102	26-24	4	0.492	0.213	0.215	.020
30103	26-24	6	0.492	0.213	0.215	.020
30104	26-24	8	0.590	0.260	0.290	.020
30105	26-24	10	0.590	0.260	0.290	.020

Rings

Non-insulated

Butted Seam


<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
30000	22-18	4	0.563	0.225	0.157	.028
30001	22-18	6*	0.661	0.256	0.240	.028
30007	22-18	6	0.720	0.312	0.270	.028
30002	22-18	8*	0.661	0.256	0.240	.028
30008	22-18	8	0.720	0.312	0.270	.028
30003	22-18	10	0.720	0.312	0.270	.028
30004	22-18	1/4	0.914	0.477	0.386	.028
30005	22-18	5/16	0.914	0.477	0.386	.028
30006	22-18	3/8	1.113	0.534	0.552	.031

Brazed Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
30200	22-18	4	0.563	0.235	0.157	.030
30201	22-18	6*	0.660	0.264	0.240	.030
30207	22-18	6	0.720	0.322	0.27	.030
30202	22-18	8*	0.660	0.264	0.24	.030
30208	22-18	8	0.720	0.322	0.27	.030
30203	22-18	10	0.720	0.322	0.27	.030
30204	22-18	1/4	0.914	0.477	0.386	.030
30205	22-18	5/16	0.914	0.477	0.386	.030
30206	22-18	3/8	1.113	0.544	0.552	.030



Ring Terminals



Typical Insulated

Rings

Insulated

Vinyl Insulated

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
30500	22-18	4	0.759	0.225	0.157	.028
30501	22-18	6*	0.857	0.254	0.240	.028
30507	22-18	6	0.946	0.312	0.270	.028
30502	22-18	8*	0.857	0.254	0.240	.028
30508	22-18	8	0.946	0.312	0.270	.028
30503	22-18	10	0.946	.0312	0.240	.028
30504	22-18	1/4	1.110	0.467	0.386	.028
30505	22-18	5/16	1.110	0.467	0.386	.028
30506	22-18	3/8	1.309	0.534	0.552	.031

Nylon w/Extra Sleeve

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
30700	22-18	4	0.855	0.235	0.157	.028
30701	22-18	6*	0.953	0.264	0.240	.028
30707	22-18	6	1.027	0.327	0.270	.028
30702	22-18	8*	0.953	0.264	0.240	.028
30708	22-18	8	1.027	0.327	0.270	.028
30703	22-18	10	1.027	0.329	0.270	.028
30704	22-18	1/4	1.206	0.477	0.386	.028
30705	22-18	5/16	1.206	0.477	0.386	.028
30706	22-18	3/8	1.405	0.544	0.552	.028

Rings


Non-insulated

Butted Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
31000	16-14	4	0.639	0.250	0.209	.031
31001	16-14	6*	0.639	0.250	0.209	.031
31008	16-14	6	0.730	0.312	0.285	.031
31009	16-14	8*	0.639	0.250	0.209	.031
31002	16-14	8	0.730	0.312	0.285	.031
31003	16-14	10	0.730	0.312	0.285	.031
31004	16-14	1/4	0.916	0.312	0.388	.031
31005	16-14	5/16	0.916	0.467	0.388	.031
31006	16-14	3/8	1.115	0.467	0.544	.031



Ring Terminals



Typical Insulated

Rings

Non-insulated

Brazed Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
31200	16-14	4	0.639	0.260	0.209	.030
31201	16-14	6*	0.639	0.260	0.209	.030
31208	16-14	6	0.730	0.322	0.285	.030
31209	16-14	8*	0.639	0.260	0.209	.030
31202	16-14	8	0.730	0.322	0.285	.030
31203	16-14	10	0.740	0.310	0.330	.030
31204	16-14	1/4	0.890	0.470	0.400	.030
31205	16-14	5/16	0.916	0.477	0.388	.030
31206	16-14	3/8	1.115	0.544	0.554	.030
31207	16-14	1/2	1.122	0.748	0.571	.033

Insulated

Vinyl Insulated


<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
31500	16-14	4	0.833	0.260	0.209	.030
31501	16-14	6*	0.833	0.260	0.209	.030
31508	16-14	6	0.924	0.322	0.285	.030
31509	16-14	8*	0.890	0.322	0.285	.030
31502	16-14	8	0.800	0.260	0.209	.030
31503	16-14	10	0.969	0.252	0.310	.030
31504	16-14	1/4	1.110	0.477	0.388	.030
31505	16-14	5/16	1.110	0.477	0.388	.030
31506	16-14	3/8	1.309	0.544	0.554	.030
31507	16-14	1/2	1.309	0.748	0.570	.030

Nylon w/Extra Sleeve

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
31700	16-14	4	0.835	0.260	0.209	.030
31701	16-14	6*	0.835	0.260	0.209	.030
31708	16-14	6	0.926	0.322	0.285	.030
31709	16-14	8*	0.833	0.260	0.209	.030
31702	16-14	8	0.924	0.322	0.285	.030
31703	16-14	10	0.971	0.352	0.310	.030
31704	16-14	1/4	1.112	0.477	0.388	.030
31705	16-14	5/16	1.112	0.477	0.388	.030
31706	16-14	3/8	1.311	0.544	0.554	.030
31707	16-14	1/2	1.339	0.748	0.570	.030



Ring Terminals



Typical Insulated

Rings

Non-insulated

Butted Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
32000	12-10	6*	0.741	0.292	0.306	.040
32007	12-10	6	0.785	0.385	0.303	.040
32001	12-10	8*	0.741	0.292	0.306	.040
32008	12-10	8	0.785	0.385	0.303	.040
32002	12-10	10	0.785	0.385	0.303	.040
32003	12-10	1/4	0.952	0.540	0.393	.040
32004	12-10	5/16	0.952	0.540	0.393	.040
32005	12-10	3/8	1.056	0.598	0.566	.040
32006	12-10	1/2	1.280	0.760	0.611	.040

Brazed Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
32200	12-10	6*	0.741	0.292	0.306	.040
32207	12-10	6	0.785	0.385	0.303	.040
32201	12-10	8*	0.741	0.292	0.306	.040
32208	12-10	8	0.785	0.385	0.303	.040
32202	12-10	10	0.785	0.385	0.303	.040
32203	12-10	1/4	0.952	0.540	0.393	.040
32204	12-10	5/16	0.952	0.540	0.393	.040
32205	12-10	3/8	1.056	0.598	0.566	.040
32206	12-10	1/2	1.280	0.760	0.611	.040


Insulated

Vinyl Insulated

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
32500	12-10	6*	1.032	0.292	0.306	.040
32507	12-10	6	1.076	0.385	0.303	.040
32501	12-10	8*	1.032	0.292	0.303	.040
32508	12-10	8	1.076	0.385	0.303	.040
32502	12-10	10	1.076	0.385	0.303	.040
32503	12-10	1/4	1.243	0.540	0.393	.040
32504	12-10	5/16	1.347	0.598	0.566	.040
32505	12-10	3/8	1.347	0.598	0.566	.040
32506	12-10	1/2	1.571	0.760	0.611	.040



Ring Terminals



Typical Insulated

Rings

Insulated

Nylon w/Extra Sleeve

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
32700	12-10	6*	1.161	0.282	0.306	.040
32707	12-10	6	1.161	0.282	0.306	.040
32701	12-10	8*	1.161	0.282	0.306	.040
32708	12-10	8	1.205	0.375	0.303	.040
32702	12-10	10	1.205	0.375	0.303	.040
32703	12-10	1/4	1.372	0.530	0.393	.040
32704	12-10	5/16	1.372	0.530	0.393	.040
32705	12-10	3/8	1.476	0.592	0.466	.040
32706	12-10	1/2	1.700	0.750	0.611	.040

Rings

Non-insulated

Brazed Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
33000	8	8	0.937	0.389	0.368	.050
33001	8	10	0.937	0.389	0.368	.050
33002	8	1/4	0.937	0.389	0.368	.050
33003	8	5/16	1.106	0.603	0.433	.050
33004	8	3/8	1.106	0.603	0.433	.050
33005	8	1/2	1.403	0.825	0.616	.050


Insulated

Nylon Insulated Only

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
33500	8	8	1.399	0.483	0.368	.050
33501	8	10	1.399	0.483	0.368	.050
33502	8	1/4	1.399	0.483	0.368	.050
33503	8	5/16	1.521	0.603	0.433	.050
33504	8	3/8	1.521	0.603	0.433	.050
33505	8	1/2	1.818	0.825	0.616	.050



Ring Terminals



Typical Insulated

Rings

Non-insulated

Brazed Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
34000	6	10	1.188	0.485	0.518	.060
34001	6	1/4	1.188	0.485	0.518	.060
34002	6	5/16	1.268	0.645	0.518	.060
34003	6	3/8	1.268	0.645	0.518	.060
34004	6	1/2	1.456	0.837	0.610	.060

Insulated

Nylon Insulated Only

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
34500	6	10	1.623	0.485	0.518	.060
34501	6	1/4	1.623	0.485	0.518	.060
34502	6	5/16	1.703	0.645	0.518	.060
34503	6	3/8	1.703	0.645	0.518	.060
34504	6	1/2	1.426	0.837	0.610	.060

Rings

Non-insulated

Brazed Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
35005	4	10	1.357	0.680	0.527	.072
35000	4	1/4	1.357	0.680	0.527	.072
35001	4	5/16	1.357	0.680	0.527	.072
35002	4	3/8	1.357	0.680	0.527	.072
35003	4	1/2	1.935	0.900	0.996	.072

Insulated


Nylon Insulated Only

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
35505	4	10	1.832	0.490	0.527	.072
35500	4	1/4	1.832	0.490	0.527	.072
35501	4	5/16	1.832	0.490	0.527	.072
35502	4	3/8	1.928	0.68	0.527	.072
35503	4	1/2	2.506	0.900	0.996	.072

Rings



Ring Terminals



Typical Insulated

Non-insulated

Brazed Seam

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
35020	2	1/4	1.583	0.645	0.703	.072
35021	2	5/16	1.583	0.645	0.703	.072
35022	2	3/8	1.583	0.645	0.703	.072
35023	2	1/2	1.700	0.879	0.703	.072

Insulated

Nylon Insulated Only

<u>Part No.</u>	<u>Gauge Size</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>	<u>Thickness</u>
35520	2	1/4	2.186	0.645	0.703	.072
35521	2	5/16	2.186	0.645	0.703	.072
35522	2	3/8	2.186	0.645	0.703	.072
35523	2	1/2	2.303	0.879	0.703	.072

* terminals are offered in a narrow width to be used where space is at a premium

Dimensions listed are a guide only and may not be exact. Dimensions may also change without notice. While efforts have been made to ensure the terminal dimensions listed are accurate, Waytek, Inc. does not warrant the accuracy of information included herein.