




WAYTEK

Spade Terminals



Insulated Stud

Spade

Non-insulated

Butted Seam

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30023	22-18	6	0.778	0.326	0.303
30024	22-18	8	0.778	0.326	0.303
30025	22-18	10	0.778	0.326	0.303
31023	16-14	6	0.770	0.372	0.269
31024	16-14	8	0.770	0.372	0.269
31025	16-14	10	0.770	0.372	0.269
32023	12-10	6	0.812	0.385	0.301
32024	12-10	8	0.812	0.385	0.301
32025	12-10	10	0.812	0.385	0.301

Brazed Seam

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30223	22-18	6	0.778	0.326	0.303
30224	22-18	8	0.778	0.326	0.303
30225	22-18	10	0.778	0.326	0.303
31223	16-14	6	0.770	0.372	0.269
31224	16-14	8	0.770	0.372	0.269
31225	16-14	10	0.770	0.372	0.269
32223	12-10	6	0.812	0.385	0.301
32224	12-10	8	0.812	0.385	0.301
32225	12-10	10	0.812	0.385	0.301

Insulated


Vinyl

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30523	22-18	6	0.974	0.316	0.303
30524	22-18	8	0.974	0.316	0.303
30525	22-18	10	0.974	0.316	0.303
31523	16-14	6	0.966	0.372	0.269
31524	16-14	8	0.966	0.372	0.269
31525	16-14	10	0.966	0.372	0.269
32523	12-10	6	1.232	0.375	0.301
32524	12-10	8	1.232	0.375	0.301
32525	12-10	10	1.232	0.375	0.301



WAYTEK

Spade Terminals



Insulated Stud

Spade

Insulated
Nylon

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30723	22-18	6	1.070	0.316	0.303
30724	22-18	8	1.070	0.316	0.303
30725	22-18	10	1.070	0.316	0.303
31723	16-14	6	1.062	0.362	0.269
31724	16-14	8	1.062	0.388	0.269
31725	16-14	10	1.062	0.388	0.269
32723	12-10	6	1.232	0.375	0.301
32724	12-10	8	1.232	0.375	0.301
32725	12-10	10	1.232	0.375	0.301

Flanged Block Spade

Non-Insulated
Butted Seam

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30020	22-18	6	0.635	0.301	0.207
30021	22-18	8	0.635	0.301	0.207
30022	22-18	10	0.635	0.301	0.207
31020	16-14	6	0.649	0.301	0.209
31021	16-14	8	0.649	0.301	0.209
31022	16-14	10	0.649	0.301	0.209
32020	12-10	6	0.770	0.385	0.301
32021	12-10	8	0.770	0.385	0.301
32022	12-10	10	0.770	0.385	0.301


Brazed Seam

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
-	-	-	-	-	-



WAYTEK

Spade Terminals



Insulated Stud

Flanged Block Spade

Insulated
Vinyl

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30520	22-18	6	0.830	0.301	0.207
30521	22-18	8	0.830	0.301	0.207
30522	22-18	10	0.830	0.301	0.207
31520	16-14	6	0.845	0.301	0.209
31521	16-14	8	0.845	0.301	0.209
31522	16-14	10	0.845	0.301	0.209
32520	12-10	6	1.070	0.385	0.301
32521	12-10	8	1.070	0.385	0.301
32522	12-10	10	1.070	0.385	0.301

Nylon

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30720	22-18	6	0.830	0.301	0.207
30721	22-18	8	0.830	0.301	0.207
30722	22-18	10	0.830	0.301	0.207
31720	16-14	6	0.845	0.301	0.209
31721	16-14	8	0.845	0.301	0.209
31722	16-14	10	0.845	0.301	0.209
32720	12-10	6	1.070	0.385	0.301
32721	12-10	8	1.070	0.385	0.301
32722	12-10	10	1.070	0.385	0.301

Snap Spade


Non-Insulated
Butted Seam

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30053	22-18	6	0.551	0.252	0.260
30054	22-18	8	0.630	0.280	0.299
30055	22-18	10	0.669	0.331	0.335
31053	16-14	6	0.551	0.252	0.260
31054	16-14	8	0.630	0.280	0.299
31055	16-14	10	0.669	0.331	0.335
32054	12-10	8	0.717	0.311	0.299
32055	12-10	10	0.717	0.311	0.299



WAYTEK

Spade Terminals



Insulated Stud

Non-Insulated

Brazed Seam

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30253	22-18	6	0.551	0.252	0.260
30254	22-18	8	0.630	0.280	0.299
30255	22-18	10	0.669	0.331	0.335
31253	16-14	6	0.770	0.372	0.269
31254	16-14	8	0.770	0.372	0.269
31255	16-14	10	0.770	0.372	0.269
32253	12-10	6	0.717	0.311	0.299
32254	12-10	8	0.717	0.311	0.299
32255	12-10	10	0.717	0.311	0.299

Insulated

Vinyl Insulated

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30553	22-18	6	0.770	0.250	0.260
30554	22-18	8	0.850	0.280	0.300
30555	22-18	10	0.890	0.330	0.340
31553	16-14	6	0.770	0.250	0.260
31554	16-14	8	0.850	0.280	0.300
31555	16-14	10	0.890	0.330	0.340
32553	12-10	6	1.010	0.310	0.300
32554	12-10	8	1.010	0.310	0.300
32555	12-10	10	1.010	0.310	0.300


Nylon Insulated

<u>Part No</u>	<u>Wire Gauge</u>	<u>Stud Size</u>	<u>Length</u>	<u>Width</u>	<u>Center</u>
30753	22-18	6	0.770	0.250	0.260
30754	22-18	8	0.850	0.280	0.300
30755	22-18	10	0.890	0.330	0.340
31753	16-14	6	0.770	0.250	0.260
31754	16-14	8	0.850	0.280	0.300
31755	16-14	10	0.890	0.330	0.340
32753	12-10	6	1.010	0.310	0.300
32754	12-10	8	1.010	0.310	0.300
32755	12-10	10	1.010	0.310	0.300



WAYTEK

Spade Terminals



Insulated Stud

Dimensions listed are a guide only and may not be exact. Dimensions may also change without notice. While efforts have been made to ensure the terminal dimensions listed are accurate, Waytek, Inc. does not warrant the accuracy of information included herein.